

Digital Signal Processing, Lab 5

Krzysztof Rudnicki
Student number: 307585

January 13, 2022

Chapter 1

Task 1

1.1 Task 1 code


1.2 Experiment

1.2.1 Estimation of delay


Block size	Delay [s]
1024	0.3
2048	0.4
4096	0.5
8192	0.72
16384	1

1.2.2 Graphs for 1024 block size

Signal and processed signal on one graph



Visible boundary error



1.2.3 How the block size influences delay

The bigger the block size, the longer the delay, for block sizes 4096 and lower the difference was almost indiscernible for human ear.

As we can see signals at the boundary with no filter are more or less random, we will try to change it with filters.


Chapter 2

Task 2


There is some kind of disturbance in sound at the beginning of the processed signal. This time, the smaller the block size the more of this sound we can hear. Which means that this disturbance is the representation of the processing error at block boundaries.

Lets plot data and boundary errors:

2.0.1 Signal



2.0.2 Boundary error




As we can see the boundary error was nicely decreased, especially the 'violet' signal looks promising.


2.1 Filter with z_i and z_f parameters


Lets plot data and boundary with z_i and z_f parameters:

2.1.1 Signal



2.1.2 Boundary error






Boundary error was even further reduced.

Chapter 3


Task 3

3.1 Lowpass filter experiment


I decided to do lowpass filter with 8kHz passband and 12 kHz stopband
Signal and processed signal plot:



Boundary error plot:




Boundary error plot zoom:




3.2 Bandpass filter experiment


I decided to do Bandpass filter with first stopband = 1kHz, first passband = 2 kHz, second passband = 3 kHz, and second stopband = 4 kHz Signal and processed signal plot:



Boundary error plot:



Boundary error plot zoom:




Chapter 4


Task 4

Unfortunately we had to use not the most optimal way of transforming sos by using function `sos2tf()` in order to use filter function in order to be able to receive z_i parameter from it. It is possible if we do not need the parameter to use `sosfilt()` function but for sake of consistency I opt out of this solution. I made a IIR filter with 10^{th} order and stop frequency of 10 kHz.


4.1 IIR filter without z_i




Boundary error plot:




Boundary error plot zoom:




4.2 IIR filter with z_i



Boundary error plot:



Boundary error plot zoom:



4.3 Questions

- Is it possible to correct errors now by remembering a fragment of the previous block? Yes
- If z_i is a vector, then its length must be $\max(\text{length}(a), \text{length}(b)) - 1$, why? Since in the loop first iteration skips the z_i we really start using it in second iteration so we need one less length of z_i vector than the max of one of coefficients,